

EZY-TURN® #6

PLUG VALVE SEALANT

DESCRIPTION

EZY-TURN® #6 plug valve sealant is a highly adhesive product formulated from premium food grade synthetic fluids for maximum hydrocarbon resistance over a broad temperature range. Pumpable and usable at temperatures as low as -30°F (-35°C). It also retains its firm consistency at temperatures as high as 500°F (260°C) when injected into the valve. Not suitable for oxygen service.

- Color: Green
- Biodegradable
- Corrosion resistant
- Stops galling
- Water resistant
- Biodegradable
- Nontoxic
- Pumpable

APPLICATIONS

EZY-TURN #6 is an all purpose sealant for use in any application involving aliphatic hydrocarbon product streams. **EZY-TURN #6** is resistant to water and aqueous services, but is not recommended for steam service. Ideal for use in plug valves where the temperature range of conventional vegetable oil sealants precludes their use. Particularly well suited for low temperature applications -30°F (-35°C) to 20°F (-7°C). Will not dissolve in aliphatic hydrocarbon services and prevents scoring and galling on precision valve surfaces.

Note: Not for use with oxygen or strong oxidizers such as hydrogen peroxide or sulfuric acid.

SERVICE RECOMMENDATIONS

- Aliphatic Hydrocarbons
- Crude
- Natural Gas
- LPG
- Diesel
- Dilute Acids & Bases
- Water
- Aqueous Solutions

TEMPERATURE RANGE

-30°F (-35°C) to 500°F (260°C)

PRODUCT CHARACTERISTICS

Appearance

Bulk Green
Stick Green Semi-Plastic

Penetration (ASTM D-217)

Bulk 220 Typical
Stick 80 Typical

Density (lb/gal) Typical

Bulk 9.15
Stick 10.95

Specific Gravity

Bulk 1.1
Stick 1.3

Dropping Point (ASTM D-2265)

Bulk & Stick None

Oil Separation (FTMS 791.B M.321.2) (ASTM D-6184)

Bulk 5.0 max
Stick 1.0 max

Thickener

Bulk & Stick Inorganic

Flash Point (ASTM D-92)

Bulk & Stick >450°F (232°C)

pH Range

Bulk & Stick 3 - 9

PACKAGING

Code No.	Net Wgt./Type	Unit Size
94080	B	3/8 x 1½
94081	J	1-3/8 x 8½
94082	K	1½ x 10½
94022	10 lb.	5 qt. can
94016	40 lb.	5 gal.
94024	120 lb.	15 gal.
94029	400 lb.	50 gal.

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC.
4849 HOMESTEAD RD.,
P.O. BOX 21258 (77226-1258)
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-674-7617
FAX: 713-678-4604
E-MAIL: sales@jetlube.com
www.jetlube.com

JET-LUBE, INC.

MATERIAL SAFETY DATA SHEET

Product Name: EZY-TURN® #6 Chemical Family: Synthetic based lubricating grease Use: Valve lubricant and sealant.	Manufacturer/Supplier: JET-LUBE, INC. Address: 4849 Homestead Rd., Ste. #200 Houston, TX, 77028 USA Phone: 713-674-7617 Emergency Phone: 713-674-7617 Fax: 713-678-4604 Chemtrec 24 hours (USA): 800-424-9300
---	---

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Nonhazardous Blend	103242/29408671	100	N/A	N/A	STEL: N/A
	68441667/27178161				
	122623/57556				
	112945525				

Main Hazards—Health Effects

Eyes: May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled.
Ingestion: May cause diarrhea. **Skin:** Possible rash for persons with hypersensitivity.

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

Extinguishing Media: Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. **Unsuitable Extinguishing Media:** Water jet.
Protective Equipment for Fire fighting: Self-contained breathing apparatus.

Personal Precautions: Wear gloves & protective overalls. **Environmental Precautions:** Nonhazardous **Spillage:** Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

Handling: Do not allow it to enter drains (it may clog drain) **Storage:** Do not store at elevated temperatures.

Respiratory Protection: None needed. **Hand Protection:** Protective gloves for hypersensitive persons. **Eye Protection:** Glasses, if applied to parts in motion. **Body Protection:** Overalls.

Physical State: Semisolid paste **Color:** Dk. Emerald Green **Odor:** Mild **pH:** Neutral **Boiling Range/Point °F (°C):** >600 (316)
Melting Point °F (°C): None **Flash Point (COC) °F (°C):** >450 (232) **Autoignition Temperature °F (°C):** >500 (260)
Explosive Properties: LEL: UN UEL: UN **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A
Vapor Pressure (kPa): <0.01 **% Volatiles:** Nil **Density (g/cm³):** 1.10 **Flammability:** Not flammable at ambient temperature.
OAR Value: N/A **Oxidizing Properties:** None **Water Solubility:** Not soluble **Vapor Density:** >5

Stability: Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition & extreme temps. **Materials to Avoid:** Strong inorganic & organic acids, oxidizing agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons & oxides of carbon and nitrogen. Residue mainly comprised of soot & mineral oxides.

Acute Toxicity: Not known. **Irritancy—Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.
Genotoxicity: None known. **Chronic Toxicity:** None known. **California Prop 65:** N/A **Carcinogen:** NTP: No **IARC:** No **OSHA:** No
EC Classification (67/548/EEC): No **Allergens:** None known. **LC-50:** >4000mg/l—extrapolated from component data. **LD-50:** N/A


Possible Effects: None
Behavior: Relatively well behaved. Bioaccumulation almost nil.
Environmental Fate: Highly unlikely to cause notable contamination. Nontoxic to marine or land organisms.

Product Disposal: Do not incinerate. Contact waste disposal company or local authority for advice. **Container Disposal:** Pails without liner—see Product Disposal section above. Pails with plastic liner—pail may only be disposed of via standard waste disposal services, recycled or reused. **Liner**—see Product Disposal section above.

Not classified as hazardous for transport. **D.O.T.:** Nonhazardous **UN No.:** Nonhazardous **Air Transport (ICAO & IATA):** Nonhazardous
Sea Transport (IMO & IMDG): Nonhazardous **Road & Rail Transport (ADR/RID):** Nonhazardous

Labeling Information: None needed **EC Annex 1 Classification:** Not Applicable. **R Phrases:** R22—harmful if swallowed.
S Phrases: None applicable, as known. **Ozone Depleting Chemicals:** Not applicable. **TSCA:** All components are listed.
WHMIS (Canada): Not controlled **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Section 313):** N/A
CERCLA: Nonhazardous **RCRA Hazard Class:** Nonhazardous **SARA 311/312:** None **TSCA 12B Components:** None

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

Signature: 
Prepared by: Donald A. Oldiges
Date Issued: January 19, 2004

As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

LEGEND	
I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	IX. PHYSICAL AND CHEMICAL PROPERTIES
II. COMPOSITION INFORMATION ON INGREDIENTS	X. STABILITY AND REACTIVITY
III. HAZARDS IDENTIFICATION	XI. TOXICOLOGICAL INFORMATION
IV. FIRST AID MEASURES	XII. ECOLOGICAL INFORMATION
V. FIRE FIGHTING MEASURES	XIII. WASTE DISPOSAL
VI. ACCIDENTAL RELEASE MEASURES	XIV. TRANSPORT INFORMATION
VII. HANDLING AND STORAGE	XV. REGULATORY INFORMATION
VIII. EXPOSURE CONTROL/PERSONAL PROTECTION	XVI. OTHER INFORMATION

HMIS SYMBOL

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PPI	

NFPA SYMBOL

