

# EZY-TURN® HI-TEMP

## GATE VALVE SEALANT FOR HI-TEMP SERVICE

### DESCRIPTION

**EZY-TURN® HI-TEMP** is a premium nonmelting, synthetic based lubricant and sealant for use in a wide variety of valve types utilized in high temperature services like geothermal well heads, steam, petroleum refineries, etc. The high viscosity synthetic base fluid is unaffected by acids, oils, CO<sub>2</sub>, H<sub>2</sub>S, glycols, caustics, water, steam, alcohols and other similar solvents. **EZY-TURN HI-TEMP** is fortified with antioxidants and rust inhibitors to augment the natural film forming and antioxidant properties of the synthetic base fluid.

**EZY-TURN HI-TEMP** provides optimum sealability, lubricity and torque reduction. The high viscosity base fluid provides excellent fluid film lubrication even under extreme pressure. The synergistic blend of graphite and MoS<sub>2</sub> further enhances both the sealing and lubrication properties of this product. At extreme temperatures where the fluids are lost, these solids provide solid film lubrication to maintain usable operating torques on the valves. The inorganic, nonsoap thickener allows for excellent chemical resistance while maintaining excellent mechanical stability.

- Color: Black
- Synthetic Base
- Seals, Lubricates
- Oxidation Resistant
- Injectable
- Nonhazardous, Nontoxic
- <5% loss after 24 hrs @ 450°F(232°C), typ.
- Synergistic Blend of MoS<sub>2</sub> & Graphite

**Note:** *Not for use with oxygen or strong oxidizers such as hydrogen peroxide or sulfuric acid.*

### TEMPERATURE RANGE

-25°F (-32°C) to 600°F (316°C)

### PRODUCT CHARACTERISTICS

Appearance	Black sticky paste
Penetration	210-240 (ASTM D-217), mm x 10 <sup>-1</sup>
Density (lb/gal), Typical	8.4
Specific Gravity, Typical	1.0
Dropping Point	None (ASTM D-2265), °F (°C)
Oil Separation Wt. %	3.0 max (FTMS 791.B M.321.2) (ASTM D-6184)
Flash Point F° (C°)	>600 (316) (ASTM D-92)
pH Range	2 - 12

### PACKAGING

Code No.	Net Wt.	Unit Size
91822	10 lb.	5 qt.
91816	35 lb.	5 gal.
91824	120 lb.	15 gal.
91829	400 lb.	50 gal.

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC.  
4849 HOMESTEAD RD.,  
P.O. BOX 21258 (77226-1258)  
HOUSTON, TX 77028

WATS: 800-538-5823  
PHONE: 713-674-7617  
FAX: 713-678-4604  
E-MAIL: [sales@jetlube.com](mailto:sales@jetlube.com)  
[www.jetlube.com](http://www.jetlube.com)

# JET-LUBE, INC.

## MATERIAL SAFETY DATA SHEET

**Product Name:** EZY-TURN® HI-TEMP  
**Chemical Family:** Synthetic lubricant  
**Use:** Lubricant for high temperature service

**Manufacturer/Supplier:** JET-LUBE, INC.  
**Address:** 4849 Homestead Rd., Ste. #200  
 Houston, TX, 77028 USA **Phone:** 713-674-7617  
**Emergency Phone:** 713-674-7617 **Fax:** 713-678-4604  
**Chemtrec 24 hours (USA):** 800-424-9300

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Nonhazardous Blend	103242/68441667	60-100	N/A	N/A	STEL: N/A
	68037014/112945525				
	7782425/68411461				
	1317335/26780961				

**Main Hazards—Health Effects**

**Eyes:** May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled.  
**Ingestion:** May cause diarrhea. **Skin:** Possible rash for persons with hypersensitivity.

**Eyes:** Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

**Extinguishing Media:** Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. **Unsuitable Extinguishing Media:** Water jet.  
**Protective Equipment for Fire fighting:** Self-contained breathing apparatus.

**Personal Precautions:** Wear gloves & protective overalls. **Environmental Precautions:** Nonhazardous **Spillage:** Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

**Handling:** Do not allow it to enter drains (it may clog drain) **Storage:** Do not store at elevated temperatures.

**Respiratory Protection:** None needed. **Hand Protection:** Protective gloves for hypersensitive persons. **Eye Protection:** Glasses, if applied to parts in motion. **Body Protection:** Overalls.

**Physical State:** Viscous, sticky paste **Color:** Black **Odor:** Mild **pH:** Neutral **Boiling Range/Point °F (°C):** >600 (316)  
**Melting Point °F (°C):** None **Flash Point (COC) °F (°C):** >600 (316) **Autoignition Temperature °F (°C):** >600 (316)  
**Explosive Properties:** LEL: 0.9% UEL: 7% **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A  
**Vapor Pressure (kPa):** <0.01 **% Volatiles:** Nil **Density (g/cm³):** 1.0 **Flammability:** Not flammable at ambient temperature.  
**OAR Value:** N/A **Oxidizing Properties:** None **Water Solubility:** Not soluble **Vapor Density:** >5

**Stability:** Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition & extreme temps. **Materials to Avoid:** Strong inorganic & organic acids, oxidizing agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons & oxides of carbon. Residue mainly comprised of soot & mineral oxides.

**Acute Toxicity:** Not known. **Irritancy—Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.  
**Genotoxicity:** None known. **Chronic Toxicity:** None known. **California Prop 65:** N/A **Carcinogen:** NTP: No IARC: No OSHA: No  
**EC Class (67/548/EEC):** No **Allergens:** None known. **LC-50:** >4000mg/l-extrapolated from component data (mysidopsis bahia). **LD-50:** N/A

**Possible Effects:** None

**Behavior:** Relatively well behaved. Bioaccumulation almost nil.

**Environmental Fate:** Highly unlikely to cause notable contamination. Nontoxic to marine or land organisms.

**Product Disposal:** Do not incinerate. Contact waste disposal company or local authority for advice. **Container Disposal:** Pails without liner—see Product Disposal section above. Pails with plastic liner—pail may only be disposed of via standard waste disposal services, recycled or reused. **Liner—**see Product Disposal section above.

Not classified as hazardous for transport. **D.O.T.:** Nonhazardous **UN No.:** Nonhazardous **Air Transport (ICAO & IATA):** Nonhazardous  
**Sea Transport (IMO & IMDG):** Nonhazardous **Road & Rail Transport (ADR/RID):** Nonhazardous


**Labeling Information:** None needed **EC Annex 1 Classification:** Not Applicable. **R Phrases:** R22—harmful if swallowed.

**S Phrases:** None applicable, as known. **Ozone Depleting Chemicals:** Not applicable. **TSCA:** All components are listed.

**WHMIS (Canada):** Not controlled **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Section 313):** N/A

**CERCLA:** Nonhazardous **RCRA Hazard Class:** Nonhazardous **SARA 311/312:** None **TSCA 12B Components:** None

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

Signature:   
 Prepared by: Donald A. Oldiges  
 Date Issued: January 19, 2004

As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

LEGEND	
I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	IX. PHYSICAL AND CHEMICAL PROPERTIES
II. COMPOSITION INFORMATION ON INGREDIENTS	X. STABILITY AND REACTIVITY
III. HAZARDS IDENTIFICATION	XI. TOXICOLOGICAL INFORMATION
IV. FIRST AID MEASURES	XII. ECOLOGICAL INFORMATION
V. FIRE FIGHTING MEASURES	XIII. WASTE DISPOSAL
VI. ACCIDENTAL RELEASE MEASURES	XIV. TRANSPORT INFORMATION
VII. HANDLING AND STORAGE	XV. REGULATORY INFORMATION
VIII. EXPOSURE CONTROL/PERSONAL PROTECTION	XVI. OTHER INFORMATION

**HMIS SYMBOL**

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PPI	

**NFPA SYMBOL**



PERSONAL PROTECTION INDEX