

ALCO-EP™

PREMIUM MULTIPURPOSE GREASE

DESCRIPTION

ALCO-EP™ Premium Multipurpose Grease is a versatile aluminum complex grease with a high level of rust and oxidation inhibitors. **ALCO-EP** also contains molybdenum disulfide (MoS₂) and graphite, which plate out to resist metal-to-metal contact in boundary modes of lubrication.

ALCO-EP provides superior wear protection against extreme pressure and is highly water resistant. Its 60 pound rating in the Timken load test proves **ALCO-EP** to have excellent load-carrying ability.

- Protects against rust and corrosion to allow long service life
- Dropping Point 500°F (260°C)
- Operating Range from -25°F (-32°C) to 450°F (232°C)
- Contains Molybdenum Disulfide (MoS₂) and graphite which plate out to resist metal-to-metal contact
- Protects against extreme pressure, shock load, welding and scoring
- Forms a protective barrier to reduce wear and extend service life

APPLICATIONS

ALCO-EP Multipurpose Grease is designed for friction and anti-friction bearings, bushings, chassis points, U-joints, pivot pins, and a wide range of other industrial, fleet and equipment applications.

PRODUCT CHARACTERISTICS

Thickener	Aluminum Complex
Fluid Type	Lubricating Oil
Color/Appearance	Opaque Black Grease
Dropping Point (ASTM D-566)	500°F (260°C)
Specific Gravity	0.94
Density (lb/gal)	7.80
Additive Type	Graphite/MoS ₂ /Organic/R&O
Flash Point (ASTM D-92)	>430°F (221°C)
Autoignition Point (CALCULATED)	>500°F (260°C)
NLGI Grade	2
Penetration @77°F (ASTM D-217)	265-295
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	500
Load Wear Index	80
Wear Scar Diameter (ASTM D-2266)	0.6
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hours	<5.0
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	90-110

PACKAGING

Code No.	Container Size	Container
37050	14 oz.	Cartridge
37016	35 lb.	Pail
37024	120 lb.	Drum
37029	400 lb.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com