

EASY-CLEAN[®] LIQUID

ALKALINE CLEANER & DEGREASER CONCENTRATE

DESCRIPTION

EASY-CLEAN LIQUID is an alkaline-based cleaner/degreaser that uniquely combines cleaning agents with newly-developed emulsifying technology to provide a product that can effectively remove carbon, grease, oil, and other organic deposits while being both safe and ozone friendly. EASY-CLEAN LIQUID is tomorrow's answer to today's cleaning problems - totally effective yet safe for our environment and atmosphere. Use by pouring a five gallon pail into a drum then dilute with water filling the drum.

Biodegradable	Noncombustible	Nonflammable
Nonfuming	Nontoxic	Water Soluble

EASY-CLEAN LIQUID contains no 1:1:1 Trichloroethane, Fluorocarbons or SARA Title III, Section 313, Part 372 listed ingredients and contains no acids, chlorides, phosphates, or TTO's (Total Toxic Organic Compounds).

EASY-CLEAN LIQUID is the most effective cleaner/degreaser for heavy-duty industrial services available and can be used for parts degreasing, pressure washing, steam cleaning, ultrasound cleaning, or simply by brushing or spraying and then rinsing with water or wiping clean. In its concentrated form, EASY-CLEAN LIQUID could be corrosive to aluminum and its alloys.

APPLICATIONS

Construction	Oilfield Equipment	Metal Fabrication
Industrial	Residential	Marine
Utilities		

DILUTION RATIOS

EASY-CLEAN LIQUID may be diluted with ordinary tap water or salt water (with reduced affect). Dilution ratios will vary greatly depending on the amount of buildup, temperature, and speed required to complete the job. Suggested dilution ratios of water to EASY-CLEAN LIQUID:

<u>DILUTE</u>	<u>EQUIPMENT</u>
E-C Liquid to water	
1:10	Drilling and Construction Equipment
1:30	Upholstery, Interiors, Carpet
1:40	Fuel Oil Truck Bodies, General Cleaning High Pressure Sprayers
1:50	150-300 psi Cold Water
1:100	150-300 psi Hot Water
1:100	500-800 psi Cold Water
1:200	500-800 psi Hot Water

RINSE AND WIPE DRY - TEST FOR COLOR FASTNESS

PRODUCT CHARACTERISTICS

Specific Gravity	1.07
pH	14
Viscosity (Cps)	4.5
Flash Point (PMCC Closed Cup)	None to 212°F
(ASTM D93)	
Auto Ignition Point	None to 500°F
Vapor Pressure @ 20°C)	Composite <.04
Evaporation Rate	<1 (Butyl Acetate = 1)
Vapor Density (Air = 1)	>1
Boiling Point	212°F (100°C)
Freezing Point	28°F
VOC	0 g/L

PACKAGING

Code No.	Container Size	Container
30035	5 gal.	Jug
30029	50 gal.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

1211

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com