



# EZY-OPEN™ LIQUID VALVE PENETRANT

## DESCRIPTION

**EZY-OPEN™** Liquid valve penetrant is designed to penetrate scale, rust, corrosion and old oxidized hardened valve lubricants which can disable or make valves extremely difficult to operate. **EZY-OPEN** can be purchased as a soft gel or as a liquid specifically formulated from a select group of non-flammable, nontoxic and biodegradable fluids capable of softening or dissolving valve lubricants and sealants, residual gums, lacquer, scale and corrosion deposits.

In addition to the fluids selected, **EZY-OPEN** contains a powerful dispersant and detergent to aid in the removal of gum and lacquer, metal wetting agents to aid in the penetration of scale and rust, and PTFE to reduce the torque required to break the valve free. When the valve operates freely, the appropriate EZY-TURN® valve sealant product should be injected into the valve to provide long term lubrication and sealing.

- Color: Amber
- Biodegradable
- Nonhazardous
- No SARA listed components
- Reduces breaking torque
- Nonflammable
- Contains PTFE
- Environmentally Safe
- Contains dispersants and detergents
- Liquid

## APPLICATIONS

**EZY-OPEN** valve penetrant is designed to penetrate and lubricate disabled or hard to operate lubricated valves. Excellent for use in any injectable assembly to aid in disassembly.

## TEMPERATURE RANGE

-10°F (-23°C) to 400°F (204°C)

## PRODUCT CHARACTERISTICS

Appearance	Amber
Density (lb/gal) Typical	7.95 - 8.10
Base Fluid Viscosity cSt @ 40°C	22 Typ.
Specific Gravity	0.96
Dropping Point (ASTM D-2265)	Not Applicable
Additives	PTFE & dispersant/ detergents
Flash Point, °F (°C) (ASTM D-92)	>180 (82)
Pour Point, °F (°C) (ASTM D-97)	-10 (-23)
Fluid Types	Vegetable and Ester

**For package types and part numbers contact [sales@jetlube.com](mailto:sales@jetlube.com).**

## LIMITED WARRANTY

For warranty information please visit [http://www.jetlube.com/pdf/Jet-Lube\\_Warranty.pdf](http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf)

You can also email us at [sales@jetlube.com](mailto:sales@jetlube.com) or write to the Sales Department at the address below.