



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 22-Mar-2018

Revision Date 03-Apr-2018

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name GEAR GUARD Aerosol

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended Use For industrial use only Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet-Lube LLC

Address Jet Lube LLC
930 Whitmore Drive
Rockwall, Texas USA 75087
TEL: +1-713-670-5700 (8am-5pm CST)

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone Number 1-800-699-6318

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

| | |
|---|----------------|
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin sensitization | Category 1 |
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Aspiration toxicity | Category 1 |
| Gases Under Pressure | Compressed Gas |



Appearance Black

Physical state Liquid spray

Odor Solvent

GHS Label elements, including precautionary statements

Danger

Hazard statements

Harmful if inhaled
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May be fatal if swallowed and enters airways
Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)

Skin

IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Causes mild skin irritation Toxic to aquatic life Harmful to aquatic life with long lasting effects

Unknown acute toxicity 99.159 % of the mixture consists of ingredient(s) of unknown toxicity
91.659 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

99.159 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 99.159 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 99.159 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 86.35 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

| Chemical name | CAS-No | Percent | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|--|------------|---------|--|---|
| Petroleum gases | 68476-85-7 | 23-28 | - | - |
| Petroleum distillates, hydrotreated light | 64742-47-8 | 20-25 | - | - |
| Asphalt | 8052-42-4 | 20-25 | - | - |
| Petroleum distillates, hydrotreated light naphthenic | 64742-53-6 | 10-15 | - | - |
| Acetone | 67-64-1 | 5-10 | - | - |
| Graphite | 7782-42-5 | 1-5 | - | - |
| 1,3,4-Thiadiazole, 2,5-bis(octyldithio)- | 13539-13-4 | 1-5 | - | - |

4. FIRST AID MEASURES

First aid measures

General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion

Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as

required. Avoid breathing vapors or mists. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge None.

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH | |
|---|---|--|---|--|
| Petroleum gases 68476-85-7 | TWA: 1000 ppm | TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ | IDLH: 2000 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ | |
| Petroleum distillates, hydrotreated light 64742-47-8 | TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist) | TWA: 5 mg/m ³ (as oil mist) | | |
| Asphalt 8052-42-4 | TWA: 0.5 mg/m ³ benzene-soluble aerosol fume, inhalable particulate matter | - | Ceiling: 5 mg/m ³ fume 15 min | |
| Petroleum distillates, hydrotreated light naphthenic 64742-53-6 | 5 mg/m ³ (as oil mist) 2 mg/m ³ (inhalable) | 5 mg/m ³ (as oil mist) | | |
| Acetone 67-64-1 | STEL = 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 1800 mg/m ³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m ³ | IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³ | |
| Graphite 7782-42-5 | TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers | TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural | IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust | |
| Chemical name | Alberta | British Columbia | Ontario TWAEV | Quebec |
| Petroleum gases 68476-85-7 | TWA: 1000 ppm STEL: 1500 ppm | TWA: 1000 ppm STEL: 1250 ppm | TWA: 1000 ppm | TWA: 1000 ppm TWA: 1800 mg/m ³ |
| Petroleum distillates, | | TWA: 200 mg/m ³ | | |

| | | | | |
|----------------------------------|--|-------------------------------|--|---|
| hydrotreated light 64742-47-8 | | Skin | | |
| Asphalt 8052-42-4 | TWA: 5 mg/m ³ | TWA: 0.5 mg/m ³ | TWA: 0.5 mg/m ³ | TWA: 5 mg/m ³ |
| Acetone 67-64-1 | TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 750 ppm STEL: 1800 mg/m ³ | TWA: 250 ppm STEL: 500 ppm | TWA: 500 ppm TWA: 250 ppm STEL: 750 ppm STEL: 500 ppm | TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³ |
| Graphite 7782-42-5 | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ |

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Neoprene gloves. Nitrile rubber. Viton™.

Skin and body protection Wear suitable protective clothing. Lightweight protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Liquid spray
Appearance Black
Odor Solvent
Color No information available
Odor Threshold No information available

| <u>Property</u> | <u>Values</u> | <u>Remarks Method</u> |
|-------------------------------|-------------------|-----------------------|
| pH | 7 | |
| Melting / freezing point | No data available | None known |
| Boiling point / boiling range | >315 | None known |
| Flash Point | No data available | None known |
| Evaporation Rate | No data available | None known |
| Flammability (solid, gas) | No data available | None known |
| Flammability Limit in Air | No data available | None known |
| Upper flammability limit | No data available | |
| Lower flammability limit | No data available | |
| Vapor pressure | No data available | None known |
| Vapor density | No data available | None known |
| Relative density | 1.23 | |
| Water Solubility | Negligible | |
| Solubility(ies) | No data available | None known |



| | | |
|--|--------------------------|------------|
| Partition coefficient: n-octanol/water | Not Applicable | |
| Autoignition temperature | No data available | None known |
| Decomposition temperature | No data available | None known |
| Kinematic viscosity | No data available | None known |
| Dynamic viscosity | 1000 | |
| Explosive properties | No information available | |
| Oxidizing properties | No information available | |

Other Information

| | |
|----------------------------|--------------------------|
| Softening Point | No information available |
| Molecular Weight | No information available |
| VOC Content (%) | No information available |
| Liquid Density | No information available |
| Bulk Density | No information available |
| Particle Size | No information available |
| Particle Size Distribution | No information available |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | No information available. |
| Chemical stability | Stable under normal conditions. |
| Possibility of Hazardous Reactions | None under normal processing. |
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Conditions to avoid | Excessive heat. |
| Incompatible materials | None known based on information supplied. |
| Hazardous Decomposition Products | Carbon oxides. |

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

| | |
|---------------------|---|
| Inhalation | Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). |
| Eye contact | Specific test data for the substance or mixture is not available. May cause irritation. |
| Skin contact | Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking. |
| Ingestion | Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. |

Information on toxicological effects

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6,450.00 mg/kg
ATEmix (inhalation-dust/mist) 3.80 mg/L

Unknown acute toxicity 99.159 % of the mixture consists of ingredient(s) of unknown toxicity
 91.659 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 99.159 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 99.159 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 99.159 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 86.35 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|----------------------|--------------------------|--|
| Petroleum distillates, hydrotreated light | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat) 4 h |
| Asphalt | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 94.4 mg/m ³ (Rat) 4.5 h |
| Petroleum distillates, hydrotreated light naphthenic | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 2180 mg/m ³ (Rat) 4 h |
| Acetone | = 5800 mg/kg (Rat) | > 15700 mg/kg (Rabbit) | = 50100 mg/m ³ (Rat) 8 h |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity Classification based on data available for ingredients. Contains a known or suspected mutagen.

Carcinogenicity Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|--|-------|----------|-------|------|
| Asphalt 8052-42-4 | - | Group 2B | - | X |
| Petroleum distillates, hydrotreated light naphthenic 64742-53-6 | A2 | Group 1 | Known | X |

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.



STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

| Chemical name | Toxicity to Algae | Toxicity to Fish | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|--|-------------------|---|----------------------------|---|
| Petroleum distillates, hydrotreated light | - | LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss) | - | LC50 96 h: = 4720 mg/L (Den-dronereides heteropoda) |
| Petroleum distillates, hydrotreated light naphthenic | - | LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss) | - | EC50 48 h: > 1000 mg/L (Daphnia magna) |
| Acetone | - | 96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus) | EC50 = 14500 mg/L 15 min | 48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L |

Persistence and Degradability No information available.

Bioaccumulation

| Chemical name | Log Pow |
|--|---------|
| Petroleum gases | 2.8 |
| Asphalt | 6 |
| Petroleum distillates, hydrotreated light naphthenic | > 3.5 |
| Acetone | -0.24 |

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number U002



California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical name | California Hazardous Waste |
|--------------------|----------------------------|
| Acetone 67-64-1 | Ignitable |

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.2
 Description UN1950, AEROSOLS, 2.2
 Emergency Response Guide Number 126

TDG

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.2
 Packing Group None
 Description UN1950, AEROSOLS, 2.2

MEX

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.2
 Description UN1950, AEROSOLS, 2.2

ICAO

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.2
 Description UN1950, AEROSOLS, 2.2

IATA

UN-No. UN1950
 Proper Shipping Name AEROSOLS, NON-FLAMMABLE
 Hazard Class 2.2
 Packing Group None
 ERG Code 2L
 Description UN1950, AEROSOLS, NON-FLAMMABLE, 2.2

IMDG/IMO

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2
 Packing Group None
 EmS-No. F-D, S-U
 Description UN1950, AEROSOLS, 2.2

RID

UN-No. UN1950



| | |
|----------------------|-----------------------|
| Proper Shipping Name | AEROSOLS |
| Hazard Class | 2.2 |
| Classification code | 5A |
| Description | UN1950, AEROSOLS, 2.2 |
| ADR/RID-Labels | 2.2 |

ADR

| | |
|-------------------------|----------------------------|
| UN-No. | UN1950 |
| Proper Shipping Name | AEROSOLS |
| Hazard Class | 2.2 |
| Classification code | 5A |
| Tunnel restriction code | (E) |
| Description | UN1950, AEROSOLS, 2.2, (E) |

ADN

| | |
|----------------------|-----------------------|
| UN-No. | UN1950 |
| Proper Shipping Name | AEROSOLS |
| Hazard Class | 2.2 |
| Classification code | 5A |
| Special Provisions | 190, 327, 344, 625 |
| Description | UN1950, AEROSOLS, 2.2 |
| Hazard Labels | 2.2 |
| Limited Quantity | 1 L |
| Ventilation | VE04 |

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

| | |
|----------------------|---|
| TSCA | Complies. |
| DSL/NDSL | Complies. |
| EINECS/ELINCS | Contact supplier for inventory compliance status. |
| ENCS | Contact supplier for inventory compliance status. |
| KECL | Contact supplier for inventory compliance status. |
| PICCS | Contact supplier for inventory compliance status. |
| AICS | Complies. |

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name | CAS-No | Percent | SARA 313 - Threshold Values % |
|---------------------|-----------|---------|-------------------------------|
| Asphalt - 8052-42-4 | 8052-42-4 | 20-25 | 0.1 |

| | |
|-----------------------------------|----|
| Acute Health Hazard | No |
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|--------------------|--------------------------|------------------------------------|--|
| Acetone 67-64-1 | 5000 lb | | RQ= 2270 kg final RQ RQ= 5000 lb final RQ |

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

| Chemical name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|--|------------|---------------|--------------|--------------|----------|
| Petroleum gases 68476-85-7 | X | X | X | X | |
| Asphalt 8052-42-4 | X | X | X | X | X |
| Petroleum distillates, hydrotreated light naphthenic 64742-53-6 | | X | | | X |
| Acetone 67-64-1 | X | X | X | X | |
| Graphite 7782-42-5 | X | X | X | X | |

16. OTHER INFORMATION

| | | | | |
|-----------------------------------|----------------------------------|----------------|--------------------|------------------------------------|
| NFPA | Health hazards 2 | Flammability 0 | Instability 0 | Physical and Chemical Properties - |
| HMIS | Health hazards 2 * | Flammability 0 | Physical hazards 0 | Personal Protection X |
| <i>Chronic Hazard Star Legend</i> | <i>* = Chronic Health Hazard</i> | | | |

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110



1-800-572-6501

Issuing Date 22-Mar-2018

Revision Date 03-Apr-2018

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet