

Issuing Date 03-Mar-2014

Revision Date 31-Jan-2018

Revision Number 6



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Jet-Lube® KOPR-KOTE® - Aerosol

Other means of identification

Product Code(s) 10041

Synonyms KOPR-KOTE® - Aerosol

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet-Lube LLC

Address Jet Lube, LLC
930 Whitmore Drive
Rockwall, Texas USA 75087
TEL: +1-713-670-5700 (8am-5pm CST)

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone Number Toll Free: 1-888-771-7775

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1



Flammable Aerosols	Category 1
Gases Under Pressure	Liquefied Gas

Appearance Copper Bronze**Physical state** Aerosol**Odor** Petroleum**GHS Label elements, including precautionary statements****Danger****Hazard statements**

Causes serious eye irritation

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed Causes mild skin irritation Very toxic to aquatic life with long lasting effects

Unknown acute toxicity

100 % of the mixture consists of ingredient(s) of unknown toxicity

50.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Synonyms KOPR-KOTE® - Aerosol

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	74869-21-9	45-50	-	-
Propane	74-98-6	25-30	-	-
Graphite	7782-42-5	5-10	-	-
Copper (flake)	7440-50-8	5-10	-	-
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1-5	-	-
Talc	14807-96-6	1-5	-	-
Limestone	1317-65-3	1-5	-	-
Molybdenum (IV) sulfide	1317-33-5	1-5	-	-

4. FIRST AID MEASURES

First aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)



involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge Yes.

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other Information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper (flake) 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist IDLH: 100 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist
Talc 14807-96-6	TWA: 2 mg/m ³	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³ containing no asbestos and <1% quartz TWA: 2 mg/m ³
Limestone	-	TWA: 15 mg/m ³	TWA: 5 mg/m ³ respirable dust

1317-65-3		TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 10 mg/m ³ total dust	
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ Mo inhalable particulate matter TWA: 3 mg/m ³ Mo respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ Mo	IDLH: 5000 mg/m ³ Mo	
Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³
Graphite 7782-42-5	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
Copper (flake) 7440-50-8	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³
Talc 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 3 mg/m ³
Limestone 1317-65-3	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³ STEL: 20 mg/m ³		TWA: 10 mg/m ³
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 3 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Aerosol
Appearance Copper Bronze
Odor Petroleum
Color No information available
Odor Threshold No data available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	7		



Melting / freezing point	260 °C	None known
Boiling point / boiling range	316 °C	None known
Flash Point	> 75 °C	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.881	
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	Not Applicable	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
264		
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause drowsiness or dizziness.
-------------------	--

Eye contact	Causes serious eye irritation.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Information on toxicological effects

Symptoms No information available.

Numerical measures of toxicity**Acute Toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2,280.00 mg/kg

Unknown acute toxicity 100 % of the mixture consists of ingredient(s) of unknown toxicity
 50.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	= 2280 mg/kg (Rat)	-	-
Propane	-	-	= 658 mg/L (Rat) 4 h
Solvent naphtha (petroleum), medium aliphatic	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h
Molybdenum (IV) sulfide	-	-	> 2820 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Legend

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	No information available.

12. ECOLOGICAL INFORMATION

Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to DOT

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	>1001 mg/l	96h LC50: > 2000 mg/L (Salmo gairdneri)	-	-
Copper (flake)	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio)	-	48h EC50: = 0.03 mg/L
Solvent naphtha (petroleum), medium aliphatic	96h EC50: = 450 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 800 mg/L (Pimephales promelas)	-	48h EC50: > 100 mg/L
Talc	-	96h LC50: > 100 g/L (Brachydanio rerio)	-	-

Persistence and Degradability No information available.

Bioaccumulation

Chemical name	Log Pow
Propane	2.3

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS



Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number D001

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Copper (flake) 7440-50-8	Toxic

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to DOT
Description UN1950, Aerosols, flammable, 2.1
Emergency Response Guide Number 126

TDG

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group None
Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to TDG.
Description UN1950, Aerosols, 2.1

MEX

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2
Description UN1950, Aerosols, 2.2

ICAO

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

IATA

UN-No. UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
Packing Group None
ERG Code 10L



Description UN1950, Aerosols, flammable, 2.1

IMDG/IMO

UN-No. UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Packing Group None
 EmS-No. F-D, S-U
 Description UN1950, Aerosols, 2.1, FP >75C

RID

UN-No. UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Classification code 5F
 Description UN1950 Aerosols, 2.1,
 ADR/RID-Labels 2.1

ADR

UN-No. UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Classification code 5F
 Tunnel restriction code (D)
 Description UN1950 Aerosols, 2.1,

ADN

UN-No. UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2
 Classification code 5F
 Special Provisions 190, 327, 344, 625
 Description UN1950, Aerosols, 2.1
 Hazard Labels 2.1
 Limited Quantity 1 L
 Ventilation VE01, VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.
 DSL/NDL Contact supplier for inventory compliance status.
 EINECS/ELINCS Contact supplier for inventory compliance status.
 ENCS Contact supplier for inventory compliance status.
 KECL Contact supplier for inventory compliance status.
 PICCS Contact supplier for inventory compliance status.
 AICS Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory



DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	Percent	SARA 313 - Threshold Values %
Copper (flake) - 7440-50-8	7440-50-8	5-10	1.0

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper (flake) 7440-50-8		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper (flake) 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Propane 74-98-6	X	X	X	X	-
Graphite 7782-42-5	X	X	X	X	
Copper (flake) 7440-50-8	X	X	X	X	X
Talc	X	X	X	X	X



14807-96-6					
Limestone 1317-65-3	X	X	X	X	
Molybdenum (IV) sulfide 1317-33-5		X			

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2*	Flammability 4	Physical hazards 0	Personal Protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 03-Mar-2014

Revision Date 31-Jan-2018

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

