



MAGIC WRENCH[®] AEROSOL SUPER PENETRANT

DESCRIPTION

MAGIC WRENCH[®] AEROSOL Super Penetrant attacks rust and corrosion quickly and safely to free corroded parts, loosen nuts and aid in the disassembly of mechanical components. Versatile synthetic formula penetrates, lubricates, removes moisture and protects chains, cables, slides and other moving parts. Contains no Silicones and is non-evaporative. Safe on all metals and plastics. Excellent for both food grade and non-food grade applications. Low V.O.C. (Volatile Organic Components) formula assures not only an environmentally responsible product, but more active ingredients to enhance product performance.

- NSF H-1 Registered #048230
- Penetrates Fast
- Synthetic Fluids
- Biodegradable
- Destroys Rust
- Lubricates
- Safe on Metal & Plastic
- Convenient aerosol package
- Low VOC Formula
- Silicone Free
- Ozone Safe
- Non-evaporative

APPLICATIONS

MAGIC WRENCH is a premium, synthetic product that may be used as a light machine oil, penetrating oil or rust preventive. Excellent for use on equipment such as chains, linkages, cams and slides, stirrups on bottle-filling machines, valves, pins, hinges, cables, etc. In addition, **MAGIC WRENCH** is an ideal product for the lubrication and conditioning of air tools.

NSF H-1 Registered (Reg. No. 048230). Conforms to FDA Regulation CFR 21, Section 178.3570 for incidental Food Contact.

PRODUCT CHARACTERISTICS

Spray Pattern (from 12" distance)	1" cone
Service Rating	-40°F (-40°C) to 350°F 177 (°C)
NFPA 30B Storage Class	Level III
VOC Content (Including Propellant)	83 g/Liter
Flame Extension Test	6" – 8"
Appearance	Clear, pale yellow fluid w/faint odor
Fluid Type	Ester & White Oils
ISO Viscosity Grade	32
SAE Viscosity Grade	10
Density (lbs./gal)	6.92
Specific Gravity	0.83
Flash Point (ASTM D-92)	>450°F (232°C)
Copper Strip Corrosion (ASTM D-130)	1B
Pour Point (ASTM D-97)	10°F (-12°C)

**For package types and part numbers
contact sales@jetlube.com.**

LIMITED WARRANTY

For warranty information please visit
http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.