



A CSW Industrials Company

# SAFETY DATA SHEET

Issuing Date 25-Jul-2012

Revision Date 26-Apr-2018

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** MOLY-MIST™ AEROSOL

### Other means of identification

**Product Code(s)** 160

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lubricants, Greases and Release Products

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Jet-Lube LLC

**Address** Jet Lube LLC  
930 Whitmore Drive  
Rockwall, Texas USA 75087  
TEL: +1-713-670-5700 (8am-5pm CST)

**Telephone** US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

**E-mail** Sales@jetlube.com

### Emergency telephone number

**Company Emergency Phone Number** Toll Free: 1-888-771-7775

**Emergency Telephone Number** CHEMTREC: +1-703-527-3887 (INTERNATIONAL)  
1-800-424-9300 (NORTH AMERICA)

## 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1



Germ cell mutagenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Flammable Aerosols	Category 1
Gases Under Pressure	Liquefied Gas

**Appearance** Black**Physical state** Aerosol**Odor** Ether**GHS Label elements, including precautionary statements****Danger****Hazard statements**

Harmful if inhaled  
 Causes skin irritation  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause genetic defects  
 May cause drowsiness or dizziness  
 Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Pressurized container: Do not pierce or burn, even after use  
 Do not spray on an open flame or other ignition source

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash before reuse  
 If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
 Protect from sunlight

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

May be harmful if swallowed May be harmful in contact with skin Harmful to aquatic life with long lasting effects

**Unknown acute toxicity** 90 % of the mixture consists of ingredient(s) of unknown toxicity  
 33.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 73 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 90 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 73 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 58.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Acetone	67-64-1	30-36	-	-
Petroleum distillates	68476-85-7	20-25	-	-
Methyl ethyl ketone	78-93-3	15-20	-	-
Xylenes (o-, m-, p-isomers)	1330-20-7	7-11	-	-
Bisphenol A - Epichlorohydrin polymer	25068-38-6	7-12	-	-
Molybdenum (IV) sulfide	1317-33-5	5-10	-	-
Mineral Spirits	64741-41-9	1 - 5	-	-

### 4. FIRST AID MEASURES

**First aid measures****General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

**Inhalation**

Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

**Skin contact**

In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash off



immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

**Ingestion**

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

**Self-protection of the first aider**

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Use personal protective equipment as required. See section 8 for more information.

**Most important symptoms and effects, both acute and delayed****Symptoms**

Itching. Rashes. Hives. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/or wheezing. Difficulty in breathing.

**Indication of any immediate medical attention and special treatment needed****Note to physicians**

May cause sensitization in susceptible persons. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray.

**Unsuitable extinguishing media**

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

**Specific hazards arising from the chemical**

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket. Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous Combustion Products**

Carbon oxides.

**Explosion Data**

**Sensitivity to Mechanical Impact** Yes.

**Sensitivity to Static Discharge** Yes.

**Special protective equipment for fire-fighters**

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid breathing vapors or mists.

**Other Information**

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**Environmental precautions**

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

#### Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>

		other sectors (vacated) STEL: 1000 ppm		
Petroleum distillates 68476-85-7	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	
Methyl ethyl ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m <sup>3</sup> (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>	
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>		
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m <sup>3</sup> Mo inhalable particulate matter TWA: 3 mg/m <sup>3</sup> Mo respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> Mo	IDLH: 5000 mg/m <sup>3</sup> Mo	
<b>Chemical name</b>	<b>Alberta</b>	<b>British Columbia</b>	<b>Ontario TWA/EV</b>	<b>Quebec</b>
Acetone 67-64-1	TWA: 500 ppm TWA: 1200 mg/m <sup>3</sup> STEL: 750 ppm STEL: 1800 mg/m <sup>3</sup>	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 500 ppm TWA: 1190 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2380 mg/m <sup>3</sup>
Petroleum distillates 68476-85-7	TWA: 1000 ppm STEL: 1500 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>	TWA: 50 ppm STEL: 100 ppm	TWA: 200 ppm STEL: 300 ppm	TWA: 50 ppm TWA: 150 mg/m <sup>3</sup> STEL: 100 ppm STEL: 300 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls****Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tight sealing safety goggles.

**Hand protection**

Impervious gloves. Wear suitable gloves. Viton™. Nitrile rubber.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.  
Antistatic boots.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

<b>Physical state</b>	Aerosol
<b>Appearance</b>	Black
<b>Odor</b>	Ether
<b>Color</b>	No information available
<b>Odor Threshold</b>	No data available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	7	
Melting / freezing point	-95.35 °C	None known
Boiling point / boiling range	-18 - 162 °C	None known
Flash Point	> -20 °C	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.85	
Water Solubility	Soluble in water	
Solubility(ies)	Completely soluble	None known
Partition coefficient: n-octanol/water	-0.2	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available	
Oxidizing properties	No information available	

### Other Information

<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. Excessive heat.
<b>Incompatible materials</b>	Strong acids. Strong bases. Strong oxidizing agents.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). Irritating to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Causes skin irritation. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### Information on toxicological effects

<b>Symptoms</b>	Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.
-----------------	---

### Numerical measures of toxicity

#### Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	4,206.00 mg/kg
<b>ATEmix (dermal)</b>	2,162.00 mg/kg
<b>ATEmix (inhalation-gas)</b>	4,500.00 mg/L
<b>ATEmix (inhalation-dust/mist)</b>	6.00 mg/L
<b>ATEmix (inhalation-vapor)</b>	19.00 mg/L

<b>Unknown acute toxicity</b>	90 % of the mixture consists of ingredient(s) of unknown toxicity
	33.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
	73 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
	90 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
	73 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
	58.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg ( Rat )	1700mg/kg (rabbit)	18892 mg/m <sup>3</sup>
Methyl ethyl ketone	= 2737 mg/kg ( Rat )	= 6480 mg/kg ( Rabbit )	23500 mg/m <sup>3</sup>





Xylenes (o-, m-, p- isomers)	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Bisphenol A - Epichlorohydrin polymer	11400 mg/kg ( Rat )	-	-
Molybdenum (IV) sulfide	-	-	> 2820 mg/m <sup>3</sup> ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

- Skin corrosion/irritation** Classification based on data available for ingredients. Irritating to skin.
- Serious eye damage/eye irritation** Classification based on data available for ingredients. Irritating to eyes.
- Respiratory or skin sensitization** May cause sensitization by skin contact.
- Germ cell mutagenicity** No information available.
- Carcinogenicity** Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylenes (o-, m-, p- isomers) 1330-20-7	A4	Group 3	-	-

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A4 - Not Classifiable as a Human Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 3 - Not Classifiable as to Carcinogenicity in Humans

- Reproductive toxicity** No information available.
- STOT - single exposure** May cause drowsiness or dizziness.
- STOT - repeated exposure** No information available.
- Aspiration hazard** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone	-	LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Methyl ethyl ketone	-	LC50 96 h: 3130-3320 mg/L flow-through (Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h: 4025 - 6440 mg/L Static (Daphnia magna) EC50 48 h: = 5091 mg/L (Daphnia magna) EC50 48 h: > 520 mg/L (Daphnia magna)



Xylenes (o-, m-, p- isomers)	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)	EC50 = 0.0084 mg/L 24 h	EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
Mineral Spirits	72h EC50: = 4700 mg/L (Pseudokirchneriella subcapitata)	-	-	-

**Persistence and Degradability** No information available.

**Bioaccumulation**

Chemical name	Log Pow
Acetone	-0.24
Petroleum distillates	2.8
Methyl ethyl ketone	0.29
Xylenes (o-, m-, p- isomers)	2.77 - 3.15

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**US EPA Waste Number** D001 D035 U002 U159 U239

**California Hazardous Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.



Chemical name	California Hazardous Waste
Acetone 67-64-1	Ignitable
Methyl ethyl ketone 78-93-3	Toxic Ignitable
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable

## 14. TRANSPORT INFORMATION

### DOT

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols  
**Hazard Class** 2.1  
**Description** UN1950,Aerosols ,2.1  
**Emergency Response Guide Number** 126

### TDG

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols  
**Hazard Class** 2.1  
**Packing Group** None  
**Description** UN1950,AEROSOLS,2.1

### MEX

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols  
**Hazard Class** 2.1  
**Description** UN1950 Aerosols,2.1

### ICAO

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols  
**Hazard Class** 2.1  
**Description** UN1950,Aerosols,2.1

### IATA

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols, flammable  
**Hazard Class** 2.1  
**Packing Group** None  
**ERG Code** 10L  
**Description** UN1950,Aerosols, flammable,2.1

### IMDG/IMO

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols  
**Hazard Class** 2.1  
**Packing Group** None  
**EmS-No.** F-D, S-U  
**Description** UN1950, Aerosols,2.1,FP -20C

### RID

**UN-No.** UN1950  
**Proper Shipping Name** Aerosols  
**Hazard Class** 2.1



<b>Classification code</b>	5F
<b>Description</b>	UN1950 Aerosols,2.1,
<b>ADR/RID-Labels</b>	2.1

**ADR**

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	Aerosols
<b>Hazard Class</b>	2.1
<b>Classification code</b>	5F
<b>Tunnel restriction code</b>	(D)
<b>Description</b>	UN1950 Aerosols,2.1,

**ADN**

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	Aerosols (Mixture)
<b>Hazard Class</b>	2.1
<b>Classification code</b>	5F
<b>Special Provisions</b>	190, 327, 625
<b>Description</b>	UN1950 Aerosols,2.1,,Mixture
<b>Hazard Labels</b>	2.1
<b>Limited Quantity</b>	LQ2
<b>Ventilation</b>	VE01, VE04

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**Ozone-depleting substances (ODS)** Not applicable

**Persistent Organic Pollutants** Not applicable

**Export Notification requirements** Not applicable

#### International Inventories

<b>TSCA</b>	Complies.
<b>DSL/NDSL</b>	Complies.
<b>EINECS/ELINCS</b>	Complies.
<b>ENCS</b>	Not determined.
<b>KECL</b>	Not determined.
<b>PICCS</b>	Not determined.
<b>AICS</b>	Complies.

#### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	Percent	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers) - 1330-20-7	1330-20-7	7-11	1.0

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

**CWA (Clean Water Act)**

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb			X

**CERCLA**

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl ethyl ketone 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone 67-64-1	X	X	X	X	
Petroleum distillates 68476-85-7	X	X	X	X	
Methyl ethyl ketone 78-93-3	X	X	X	X	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X	X	X
Molybdenum (IV) sulfide 1317-33-5		X			

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 2 *	<b>Flammability</b> 4	<b>Physical hazards</b> 0	<b>Personal Protection</b> X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

**Prepared By** Product Stewardship  
 23 British American Blvd.  
 Latham, NY 12110  
 1-800-572-6501

**Issuing Date** 25-Jul-2012

**Revision Date** 26-Apr-2018

**Revision Note** Initial Release

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

