



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 30-Mar-2015

Revision Date 08-Mar-2017

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name JET-LUBE® WHITE LITHIUM GREASE AEROSOL

Other means of identification

Product Code(s) 50341

UN-Number UN1950

Synonyms WHITE LITHIUM GREASE AEROSOL

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products, Sealant

Uses advised against No information available

Supplier's details

Manufacturer Address

Jet-Lube, LLC
930 Whitmore Dr.
Rockwall, Texas 75087
TEL: 972-771-1000
Toll Free: 1-800-669-6318

Emergency telephone number

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Specific Target Organ Toxicity (Repeated Exposure)	Category 1
Aspiration Toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word	Danger
-------------	--------

Hazard Statements

- Causes damage to organs through prolonged or repeated exposure
- May be fatal if swallowed and enters airways
-
- Extremely flammable aerosol
- Contains gas under pressure; may explode if heated

**Appearance** Off white**Physical State** Aerosol.**Odor** Petroleum Oil-Pungent**Precautionary Statements****Prevention**

- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use.

General Advice

- Get medical attention/advice if you feel unwell

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Storage

- Store locked up.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- Protect from sunlight. Store in a well-ventilated place

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Toxic to aquatic life with long lasting effects

0.7% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

WHITE LITHIUM GREASE AEROSOL

Chemical Name	CAS-No	Weight %	Trade secret
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	35-45	*
Petroleum distillates	68476-85-7	20-25	*
Zinc oxide	1314-13-2	2-2.5	*
Titanium dioxide	13463-67-7	0-1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
Skin Contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Not an expected route of exposure. Rinse mouth. Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. Consult a physician if necessary
Protection of First-aiders	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Aspiration into lungs can produce severe lung damage

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

Ruptured cylinders may rocket. Containers may explode when heated.

Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Contents under pressure. In case of rupture: Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapors or spray mist. Use personal protective equipment. Avoid contact with skin, eyes and inhalation of vapors.

Environmental Precautions

Environmental Precautions Prevent from entering into soil, ditches, sewers, waterways, and/ or groundwater. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid.

Methods for Cleaning Up Pick up and transfer to properly labeled containers. In case of rupture: Take up with inert, damp, noncombustible material using clean non-sparking tools and place into loosely plastic containers for later disposal

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Keep away from open flames, hot surfaces and sources of ignition. In case of rupture: Wear personal protective equipment. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Take precautionary measures against static discharges. Use only in area provided with appropriate exhaust ventilation. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. Keep away from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Products Strong acids. Amines. Oxidizing agents. Alkaline materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates 68476-85-7	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2000 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Zinc oxide 1314-13-2	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ fume (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) STEL: 10 mg/m ³ fume	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and Body Protection Antistatic boots. Wear fire/flame resistant/retardant clothing. Impervious gloves. Long sleeved clothing. Chemical resistant apron.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Appearance	Off white
Odor	Petroleum Oil-Pungent	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	Neutral	None known
Melting Point/Range	190 °C / 374 °F	None known
Boiling Point/Boiling Range	> 316 °C / 600.8 °F	None known
Flash Point	< 18 °C	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	0.90	None known
Water Solubility	Insoluble	None known
Solubility in other solvents	Largely.	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known
Flammable Properties	Not flammable	
Explosive Properties	No data available	
Oxidizing Properties	No data available	

Other information

VOC Content (%)	No data available
VOC (g/l)	546 g/liter with propellant & solvent or <70%

10. STABILITY AND REACTIVITY**Reactivity**

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Keep away from direct sunlight. Do not puncture or incinerate cans. Incompatible products.

Incompatible materials

Strong acids. Amines. Oxidizing agents. Alkaline materials.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Vapors may irritate throat and respiratory system.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	None known.
Ingestion	Not an expected route of exposure. Potential for aspiration if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Zinc oxide	> 5000 mg/kg (Rat)	-	-
Titanium dioxide	> 10000 mg/kg (Rat)	-	> 6820 mg/m ³

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.
Mutagenic Effects No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X

IARC: (International Agency for Research on Cancer)
 Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)
 X - Present

Reproductive Toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.
Aspiration Hazard No information available.

Numerical measures of toxicity - Product

Acute Toxicity 0.7% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 4593 mg/kg; Acute toxicity estimate
LD50 Dermal 7500 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	EC50 96 h: = 450 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 800 mg/L static (Pimephales promelas)		EC50 48 h: > 100 mg/L (Daphnia magna)
Zinc oxide 1314-13-2	Selenastrum capricornutum 72-hour EC50: 0.14 mg/l	Oncorhynchus mykiss 96-hour LC50: 0.14 mg/l		Daphnia magna 48-hour EC50: 0.07 mg/l

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Petroleum distillates	2.8

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT

UN-Number UN1950
Proper shipping name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1
Emergency Response Guide Number 126

TDG

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

MEX

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

ICAO

UN-Number UN1950
Proper shipping name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

IATA

UN-Number UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
ERG Code 10L
Description UN1950, Aerosols, flammable, 2.1

IMDG/IMO

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Subsidiary Class See SP63
EmS No. F-D, S-U
Description UN1950, Aerosols, 2.1 (See SP63), (18°C c.c.)

RID

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2

Classification Code 5F
Description UN1950, Aerosols, 2.1

ADR

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Classification Code 5F
Tunnel Restriction Code (D)
Description UN1950, Aerosols, 2.1, (D)

ADN

Proper Shipping Name Aerosols
Hazard Class 2
Classification Code 5F
Special Provisions 190, 327, 344, 625
Description UN1950, Aerosols, 2.1
Limited Quantity 1 L
Ventilation VE01, VE04

15. REGULATORY INFORMATION

International Inventories**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Zinc oxide	1314-13-2	2-2.5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard Yes
Reactive Hazard No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc oxide		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Solvent naphtha (petroleum), medium aliphatic	X				
Petroleum distillates	X	X	X		X
Zinc oxide	X	X	X		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	X		X		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 4	Physical Hazard 0	Personal Protection X

**Indicates a chronic health hazard.*

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 30-Mar-2015
Revision Date 08-Mar-2017
Revision Note Updated company information.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet