



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 06-Apr-2015

Revision Date 05-Feb-2018

Revision Number 4



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Z-PLATE™

Other means of identification

Product Code(s) 60541

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet-Lube LLC

Address Jet Lube, LLC
930 Whitmore Drive
Rockwall, Texas USA 75087
TEL: +1-713-670-5700 (8am-5pm CST)

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone Number 1-800-699-6318

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4



Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Flammable liquids	Category 2
Gases Under Pressure	Compressed Gas

Appearance Gray**Physical state** Aerosol**Odor** Petroleum**GHS Label elements, including precautionary statements****Danger****Hazard statements**

Harmful in contact with skin

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May cause genetic defects

May cause cancer

Highly flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

Call a POISON CENTER or doctor if you feel unwell

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed Very toxic to aquatic life with long lasting effects

Unknown acute toxicity 80.22 % of the mixture consists of ingredient(s) of unknown toxicity

62.52 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

72.92 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

80.22 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

72.92 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

69.82 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance**Mixture**

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Petroleum gases	68476-85-7	23-27	-	-
Zinc (powder)	7440-66-6	20-25	-	-
Xylenes (o-, m-, p-isomers)	1330-20-7	15-20	-	-
Acetone	67-64-1	10-15	-	-
Methyl ethyl ketone	78-93-3	5-10	-	-
Aluminum	7429-90-5	1-2	-	-

4. FIRST AID MEASURES

First aid measures**General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.



Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	CAUTION: Use of water spray when fighting fire may be inefficient.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.
-----------------------------	---

Other Information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
--------------------------	--

Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor
--------------------------------	---

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling**Advice on safe handling**

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum gases 68476-85-7	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2000 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Zinc (powder) 7440-66-6	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³	IDLH: 2500 ppm 10% LEL TWA: 250 ppm

		(vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	TWA: 590 mg/m ³	
Methyl ethyl ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	
Chemical name	Alberta	British Columbia	Ontario TWA/EV	Quebec
Petroleum gases 68476-85-7	TWA: 1000 ppm STEL: 1500 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³
Acetone 67-64-1	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 750 ppm STEL: 1800 mg/m ³	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	TWA: 50 ppm STEL: 100 ppm	TWA: 200 ppm STEL: 300 ppm	TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm STEL: 300 mg/m ³
Aluminum 7429-90-5	TWA: 10 mg/m ³	TWA: 1.0 mg/m ³	TWA: 1 mg/m ³	TWA: 10 mg/m ³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls**Engineering controls**

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tight sealing safety goggles.

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Antistatic boots.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Aerosol
Appearance	Gray
Odor	Petroleum
Color	No information available
Odor Threshold	Not applicable

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	UNKNOWN	
Melting / freezing point	-95 °C	None known
Boiling point / boiling range	-18 to 162 °C	None known
Flash Point	> -20 °C	
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.94	
Water Solubility	Insoluble	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	Not applicable	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other Information</u>		
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%) ≤498	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Excessive heat.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components). Causes serious eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Information on toxicological effects

Symptoms Redness. May cause redness and tearing of the eyes. Coughing and/ or wheezing.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3,617.00 mg/kg
ATEmix (dermal)	1,398.00 mg/kg
ATEmix (inhalation-gas)	4,518.00 mg/L
ATEmix (inhalation-dust/mist)	2.28 mg/L
ATEmix (inhalation-vapor)	14.00 mg/L

Unknown acute toxicity 80.22 % of the mixture consists of ingredient(s) of unknown toxicity

62.52 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

72.92 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

80.22 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

72.92 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

69.82 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Zinc (powder)	= 630 mg/kg (Rat)	-	-
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Methyl ethyl ketone	= 2737 mg/kg (Rat)	= 6480 mg/kg (Rabbit)	23500 mg/m ³

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Irritating to eyes.

Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	Classification based on data available for ingredients. Contains a known or suspected mutagen.
Carcinogenicity	Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylenes (o-, m-, p-isomers) 1330-20-7	A4	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Zinc (powder)	EC50 72 h: 0.09 - 0.125 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 0.11 - 0.271 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.211-0.269 mg/L semi-static (Pimephales promelas) LC50 96 h: 2.16-3.05 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.24 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.41 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 0.45 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.59 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 2.66 mg/L static (Pimephales promelas) LC50 96 h: = 3.5 mg/L static (Lepomis macrochirus)	-	EC50 48 h: 0.139 - 0.908 mg/L Static (Daphnia magna)

		LC50 96 h: = 30 mg/L (Cyprinus carpio) LC50 96 h: = 7.8 mg/L static (Cyprinus carpio)		
Xylenes (o-, m-, p-isomers)	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)	EC50 = 0.0084 mg/L 24 h	EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
Acetone	-	LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Methyl ethyl ketone	-	LC50 96 h: 3130-3320 mg/L flow-through (Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h: 4025 - 6440 mg/L Static (Daphnia magna) EC50 48 h: = 5091 mg/L (Daphnia magna) EC50 48 h: > 520 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Chemical name	Log Pow
Petroleum gases	2.8
Xylenes (o-, m-, p- isomers)	2.77 - 3.15
Acetone	-0.24
Methyl ethyl ketone	0.29

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS



Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
US EPA Waste Number	D001 D035 U239 U002 U159

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Zinc (powder) 7440-66-6	Ignitable powder
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable
Acetone 67-64-1	Ignitable
Methyl ethyl ketone 78-93-3	Toxic Ignitable
Aluminum 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION**DOT**

UN-No.	UN1950
Proper Shipping Name	Aerosols (Mixture)
Hazard Class	2.1
Packing Group	II
Description	UN1950, Aerosols , 2.1 , , Mixture
Emergency Response Guide Number	126

TDG

UN-No.	UN1950
Proper Shipping Name	Aerosols (Mixture)
Hazard Class	2.1
Packing Group	II
Description	UN1950, AEROSOLS, 2.1, Mixture

MEX

UN-No.	UN1950
Proper Shipping Name	Aerosols (Mixture)
Hazard Class	2.1
Packing Group	II
Description	UN1950 Aerosols, 2.1 , , Mixture

ICAO

UN-No.	UN1950
Proper Shipping Name	Aerosols (Mixture)
Hazard Class	2.1



Packing Group II
Description UN1950, Aerosols, 2.1, Mixture

IATA

UN-No. UN1950
Proper Shipping Name Aerosols, flammable (Mixture)
Hazard Class 2.1
Packing Group II
ERG Code 3H
Description UN1950, Aerosols, flammable, 2.1, Mixture

IMDG/IMO

UN-No. UN1950
Proper Shipping Name Aerosols (Mixture)
Hazard Class 2.1
Packing Group II
EmS-No. F-D, S-U
Marine Pollutant Product is a marine pollutant according to the criteria set by IMDG/IMO
Description UN1950, Aerosols, 2.1, Mixture, FP -20C

RID

UN-No. UN1950
Proper Shipping Name Aerosols (Mixture)
Hazard Class 2.1
Packing Group I
Classification code 5F
Description UN1950 Aerosols, 2.1, , Mixture
ADR/RID-Labels 3

ADR

UN-No. UN1950
Proper Shipping Name Aerosols (Mixture)
Hazard Class 2.1
Packing Group I
Classification code 5F
Tunnel restriction code (D/E)
Description UN1950 Aerosols, 2.1, ,, Mixture

ADN

UN-No. UN1950
Proper Shipping Name Aerosols (Mixture)
Hazard Class 2.1
Packing Group I
Classification code 5F
Special Provisions 190, 327, 625
Description UN1950 Aerosols, 2.1, , Mixture
Hazard Labels 2.1
Limited Quantity LQ2
Ventilation VE01, VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Complies.
EINECS/ELINCS	Complies.
ENCS	Complies.
KECL	Complies.
PICCS	Complies.
AICS	Complies.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	Percent	SARA 313 - Threshold Values %
Zinc (powder) - 7440-66-6	7440-66-6	20-25	1.0
Xylenes (o-, m-, p- isomers) - 1330-20-7	1330-20-7	15-20	1.0
Aluminum - 7429-90-5	7429-90-5	1-2	1.0

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc (powder) 7440-66-6		X	X	
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Zinc (powder) 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
Xylenes (o-, m-, p- isomers)	100 lb		RQ 100 lb final RQ

1330-20-7			RQ 45.4 kg final RQ
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl ethyl ketone 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Petroleum gases 68476-85-7	X	X	X	X	
Zinc (powder) 7440-66-6	X	X	X	X	
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X	X	X
Acetone 67-64-1	X	X	X	X	
Methyl ethyl ketone 78-93-3	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	

16. OTHER INFORMATION

<u>NFPA</u>	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal Protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 06-Apr-2015

Revision Date 05-Feb-2018

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

