



Z-PLATE™ AEROSOL

ZINC-RICH GALVANIZE

DESCRIPTION

Z-PLATE™ provides the protection of hot-dip galvanizing PLUS the convenience of on-the-job aerosol application. **Z-PLATE** contains 95% pure zinc and forms a tough, durable, and flexible zinc metal coating that actually bonds electrochemically with the base metal to protect against rust, rust-spreading, and corrosion.

Z-PLATE may be used indoors or outdoors and requires no surface preparation under normal circumstances. On surfaces that have experienced severe rust formation, all loose scale should be removed and the area to be treated should be wire brushed prior to **Z-PLATE's** application.

- 95% Pure Zinc
- Quick Drying
- Minimal Surface Prep
- Long Lasting
- Stops Rust and Corrosion on any Iron or Steel Surface
- Easy Aerosol Application
- Indoor/Outdoor Use
- Permanent, Flexible
- USDA Authorized

APPLICATIONS

Excellent for cosmetic repairs to welded joints, guard rails, bridges, fencing, storage tanks, pipe lines, TV towers, metal buildings, heavy equipment, heat ducts, marine, and off-shore equipment.

Z-PLATE is in full compliance with the following Military Specification: MIL-PRF-26915D (USAF).

PRODUCT CHARACTERISTICS

Spray Pattern, from 12" distance	2" to 4" cone
Propellant	Hydrocarbon
VOC Content	504g/Liter (Includes Propellant)
NFPA 30B Storage Class	Level III
Color	Grey
Solvent Type	No CFC's or Chlorinated
Resin	Epoxy Ester
Zinc Dust	
Purity	> 95%
Particle Size (% <45 microns)	100
Film Appearance	Smooth Grey
Dry Time	15 min.
Cure Time	24 hrs.
Typical Film Thickness	1 mil
Density (lbs/gal)	9.7
Specific Gravity	1.17
Flash Point	-4°F (-16°C)
Typical Coverage	2,400 sq. in / 12 oz. can 43,500 sq. in. per 1 gal

For package types and part numbers contact sales@jetlube.com.

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.